

## WH016: Forklift Inverta Push Clamp

### ● FUNCTIONS&APPLICATIONS

Designed for palletless handling.

Used to transport, load and stackable of pallets loads like plastic, concrete, fertilizer, feed, grain, cement, mail, sugar, canned goods, boxed goods, glass, push the load and take out the pallet without labor, safety and efficiently, reduce labor work.

CAPACITY@ LOAD CENTER	MODEL	MOUNTING CLASS	OPENING RANGE	LAUNCH DISTANCE	SIDE ARM WIDTH	SIDE ARM STROKE	PLATEN WIDTH	FORK DISTANCE	PUSH PLATE SIZE H*W	WEIGHT	EFFECTIVE THICKNESS	HORIZONTAL CENTER OF GRAVITY
kg@mm			(mm)	A (mm)	B (mm)	(mm)	C (mm)	D (mm)	H*W (mm)	(kg)	ET (mm)	HCG (mm)
1500@500	TCX20D-C002	III	950-1530	1320	890	100	1005	655	885x1005	1350	483	364

HYDRAULIC FLOW AND PRESSURE					
MODEL	Pressure (Bar)		Hydraulic Flow (L/min)		
	Min	Max	Min	Rec	Max
20D	35	160	19	38	57